

Technical Specs Primera TRIO all-in-one printer

ALL-IN-ONE FUNCTIONS	Print, Scan, Copy
PRINT SPEED ¹	(draft, letter): 3.1 ppm black, 2.4 ppm colour ISO Speeds: Up to 2.4 ppm black, 1.7 ppm colour
PRINT RESOLUTION	Up to 4800 x 1200 dpi
DUPLEX PRINT OPTIONS	Manual
PRINT SMART SOFTWARE	Manual duplex, print on postcard to envelope and up to legal size, single-sheet scan, borderless postcard photo
PRINT TECHNOLOGY	Thermal Inkjet
INK TYPES	Dye-based colour and black
BORDERLESS PRINTING	Yes; up to 101.6 x 152.4 mm (4" x 6")
COPY RESOLUTION	Up to 600 x 600 dpi colour and black
SCAN FILE FORMAT	Scan file type supported by software: bitmap (.bmp), JPEG (.jpg), PDF (.pdf), PNG (.png), TIFF (.tif), GIF (.gif)
SCAN SPEED	Up to 1.4 ppm (300 dpi, b&w); Up to 1.6 ppm (300 dpi, colour)
SCAN RESOLUTION	Hardware: Up to 600 x 600 dpi Optical: Up to 600 dpi
SCAN SIZE MAXIMUM	Up to 216 x 356 mm (8.5" x 14")
BIT DEPTH/GRAYSCALE LEVELS	24-bit/256
TWAIN VERSION	Version 1.9
STANDARD CONNECTIVITY	USB 2.0/3.0 compatible
MEDIA SIZES SUPPORTED	Letter, legal, folio, A4, A6, 4" x 6" photo, U.S. #10 envelope, hagaki, custom
SCANNER CAPACITY	One (Sheet, receipt, business card, etc.)
PAPER HANDLING	Up to 10 sheets input tray. Input slot on the back for feeding and printing onto light cardstocks, envelopes and photo paper
CUSTOM MEDIA SIZES	76.2 x 101.6 to 215.90 x 355.6 mm (3 x 3 to 8.5 x 14 in) Windows Vista™, 7, 8, 8.1 and 10 Intel® Celeron® processor or faster (or equivalent) 2GB RAM 1GB hard drive space CD/DVD drive if installing software from disc OSXv10.6 or higher 2 GB RAM
MINIMUM SYSTEM REQUIREMENTS (Windows®)	1 GB hard drive space CD/DVD drive if installing software from disc USB 1.1 or higher
MINIMUM SYSTEM REQUIREMENTS (Mac®)	Recommended operating temperatures: 4 °C to 32 °C (40 °F to 90 °F) Maximum operating temperatures: -40 °C to 46 °C (-40 °F to 115 °F) Recommended humidity while operating: 15% to 90% RH Maximum humidity while operating: 10% to 98% RH
OPERATING ENVIRONMENT	290 mmW x 46 mmH x 165 mmD (11.4"W x 1.8"H x 6.5"D)
PRODUCT DIMENSIONS	With no battery: 1.2 kg (2.7 lbs.) With battery: 1.27 kg (2.8 lbs.)
PRODUCT WEIGHT	Power supply type: external universal power adapter
POWER	Input voltage: 90 to 264 VAC Output voltage: 7.5 VDC @ 3.2A
WARRANTY	One-year parts and labor including one year of phone, chat and email support
WHAT'S IN THE BOX	Primera Trio Printer, Primera 31022 colour ink cartridge, Lithium-ion battery (up to 350 pages), 3-foot micro-USB to USB cable, calibration sheet and quick reference guide
REPLACEMENT INK CARTRIDGES	Primera 53376 High-Yield Color Cartridge (580 pages, draft), (260 pages, ISO) ² Primera 53377 High-Yield Black Cartridge (495 pages, draft), (185 pages, ISO) ² Primera 31020 Standard Yield Color Cartridge (175 pages, draft), (70 pages, ISO) ² Primera 31021 Standard Yield Black Cartridge (360 pages, draft), (135 pages, ISO) ²

¹ Either after first page or first set of ISO test pages using ISO/IEC 24734.

² Replacement cartridge yields are based on ISO/IEC 24711 tests in default mode printing continuously.